



AdvantaSil® - APSH-DB Double-Braided Silicone Hose

| Part # | Nominal I.D | | Wall | | O.D | |
|--------------|-------------|-------|-------|------|-------|-------|
| | (in.) | (mm) | (in.) | (mm) | (in.) | (mm) |
| APSH-DB-0500 | .500 | 12.70 | .195 | 4.95 | .890 | 22.60 |
| APSH-DB-0750 | .750 | 19.05 | .215 | 5.46 | 1.180 | 29.97 |
| APSH-DB-1000 | 1.000 | 25.40 | .215 | 5.46 | 1.430 | 36.32 |

| Part # | Working Pressure at 70°F (21.1°C) | | Burst Pressure at 70°F (21.1°C) | | Bend Radius (in.) | Standard Length (ft.) |
|--------------|--------------------------------------|-------|------------------------------------|-------|----------------------|-----------------------------|
| | PSI | Bar | PSI | Bar | | |
| APSH-DB-0500 | 150.0 | 10.34 | 600 | 41.36 | 2.5 | 50 |
| APSH-DB-0750 | 187.5 | 12.93 | 750 | 51.72 | 3.0 | 50 |
| APSH-DB-1000 | 125.0 | 8.62 | 500 | 34.48 | 3.5 | 25, 50 |

HPNE TUBING RANGE