



AdvantaSil® - APST Unreinforced Silicone Tubing

Part #	I.D		Wall		O.D (reference)		Working Pressure at 70°F (21.1°C)		Standard Available Lengths
	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(PSI)	(bar)	(ft.)
A7000591	.030	.76	.065	1.65	.160	4.06	53	3.7	50
A7001098	.063	1.59	.031	.79	.125	3.18	22	1.5	50
A7001111	.063	1.59	.063	1.59	.188	4.76	33	2.3	50
A7001280	.078	1.98	.031	.79	.141	3.58	17	1.2	50
A7001475	.094	2.38	.063	1.59	.219	5.56	25	1.7	100
A7001488	.094	2.38	.094	2.38	.281	7.14	34	2.3	100
A7001657	.125	3.18	.063	1.59	.250	6.35	23	1.6	50,100,500 spool
A7001670	.125	3.18	.094	2.38	.313	7.94	29	2.0	50
A7001683	.125	3.18	.125	3.18	.375	9.53	37	2.6	50
A7001865	.156	3.97	.125	3.18	.406	10.31	33	2.3	50
A7002021	.188	4.76	.063	1.59	.313	7.94	16	1.1	50
A7002034	.188	4.76	.094	2.38	.375	9.53	21	1.4	50
A7002047	.188	4.76	.125	3.18	.438	11.11	25	1.7	50
A7002203	.250	6.35	.063	1.59	.375	9.53	13	0.9	50, 100
A7002216	.250	6.35	.094	2.38	.438	11.11	18	1.2	50, 100, 300 spool
A7002229	.250	6.35	.125	3.18	.500	12.70	22	1.5	50,100
A7002385	.313	7.94	.063	1.59	.438	11.11	11	0.7	25,50
A7002398	.313	7.94	.094	2.38	.500	12.70	17	1.2	50,100
A7002411	.313	7.94	.125	3.18	.563	14.30	21	1.4	50,100
A7002567	.375	9.53	.063	1.59	.500	12.70	10	0.7	50,100
A7002580	.375	9.53	.094	2.38	.563	14.30	16	1.1	50,100
A7002593	.375	9.53	.125	3.18	.625	15.88	16	1.1	25,50,100,150 spool
A7002762	.500	12.70	.094	2.38	.688	17.48	11	0.8	50
A7002775	.500	12.70	.125	3.18	.750	19.05	12	0.8	50,100
A7002957	.625	15.88	.125	3.18	.875	22.23	11	0.8	50,100
A7002970	.625	15.88	.188	4.76	1.000	25.40	16	1.1	25,50
A7003139	.750	19.05	.125	3.18	1.000	25.40	10	0.7	50,100
A7003152	.750	19.05	.188	4.76	1.125	28.58	14	1.0	25,50
A7003503	1.000	25.40	.125	3.18	1.250	31.75	8	0.6	50
A7003516	1.000	25.40	.188	4.76	1.375	34.93	11	0.8	25,50
A7003529	1.000	25.40	.250	6.35	1.500	38.10	13	0.9	50

HPNE TUBING RANGE